



V110R

Technical Data | Metric



11t

MAX PAYLOAD

Portata massima / Capacité max

Max Tragfähigkeit / Max capacidad

V110R


TECHNICAL INFORMATION AND OVERALL SIZE

Informazioni tecniche e dimensioni d'ingombro

Informations techniques et taille globale

Technische information und Gesamte Größe

Información técnica y dimensiones totales



MAX PAYLOAD

Portata massima / Capacité max

Max Tragfähigkeit / Max capacidad

11.000 kg

TOTAL WEIGHT

Peso totale / Poids total

Gesamtgewicht / Peso total

11.400 kg

DIMENSIONS

Dimensioni / Dimensions

Abmessungen / Dimensiones

3765 x 1500 x 1945 mm

FRONT

Anteriore / Avant / Vorderrad / Delantera

N° 2 S.E. / 355/65 – 15"

REAR

Posteriore / Arrière / Hinterrad / Trasera

N° 2 S.E. / 250 – 15"

HYDRAULICS

Impianto idraulico (Pressione massima/Potenza motore)

Hydraulique (Pression maxi/Puissance moteur)

Hydraulik (Max Druck/Motorleistung)

Hidraulica (Presion max/Potencia motor)

220 Bar – 16 kW AC

FRONT-WHEEL DRIVE

Trazione anteriore / Traction avant

Frontantrieb / Tracción delantera

N° 2 x 6.5 kW AC

REAR STEERING

Sterzata posteriore / Direction arrière

Hintere Lenkung / Direccion trasera

800W AC - 180°

BATTERY

Batteria / Batterie / Batterie / Batterie

80V - 640 Ah

REMOVABLE COUNTERWEIGHTS

Contrappesi removibili / Contrepoids amovibles

Abnehmbare Gegengewichte / Contrapesos removibles

N° 2 x 2.100 kg

ELECTRO-HYDRAULIC BRAKES


Freni elettroidraulici / Freins électrohydrauliques

Elektrohydraulische Bremsen / Frenos electrohidráulicos

V110R

MAXIMUM PERFORMANCE AND EQUIPMENTS

Massime prestazioni ed equipaggiamenti
Performances maximales et équipements
Maximale Leistung und Ausrüstung
Máximas prestaciones y equipamiento



REFERENCE STANDARDS

Normative di riferimento / Normes de référence
Referenzstandards / Estandards de referencia

2006/42 CE
EN 13000

STANDARD

NON-MARKING TIRES

Ruote anti traccia / Roues anti-traces
Nicht-markierende Räder / Ruedas anti-marcas

VARIABLE TILT HEAD

Testa ad inclinazione variabile / Tête à inclinaison variable
Abwinkelbare Spitze / Cabezal ajustable

RADIO-CONTROL

Radiocomando / Radiocommande / Fernsteuerung / Radio control

HOOK

Gancio / Crochet / Haken / Gancho

OPTIONAL

STABILIZER CROSSBAR

Barra stabilizzatrice anteriore / Barre stabilisatrice
Vorderradabstützung / Barra estabilizadora

WINCH KIT

Kit Argano / Kit treuil / Winden-Satz / Kit de cabrestante

HYDRAULIC FOLDING JIB

Jib idraulico ripiegabile / Fléchette hydraulique repliable
Hydraulische Klappspitze / Plumín hidráulico plegable

MECHANICAL FOLDING JIB

Jib meccanico ripiegabile / Fléchette mécanique repliable
Klappbare mechanische Spitze / Plumín mecánico plegable

SELF LEVELLING FORK KIT

Kit forche autolivellanti / Kit de fourches à nivellement automatique
Selbstnivellierendes Gabelkit / Kit de horquillas autonivelantes

LITHIUM BATTERIES

Batterie al litio / Batteries au lithium
Lithiumbatterien / Baterías de litio

ATEX TRANSFORMATION

Trasformazione ATEX / Transformation ATEX
ATEX-Umwandlung / Transformación ATEX

VALLA CONNECT SYSTEM

info.valla@tadano.com

www.tadano.com

Tadano Ltd.

Kanda Square 18th Floor, 2-2-1 Kanda-Nishikicho, Chiyoda-ku, Tokyo 101-0054, Japan

Phone: +81-3-6811-7309 (International Division)

Manitex Valla S.R.L.

Via Leonardo da Vinci, 12 29016 - Careco - Piacenza - Italia.

Tel.: +39 0523 256411



Reaching new heights

